

BUILDING



# ADVANCED THERMAL IMAGING

REIMAGINED FROM THE HANDLE UP

*FLIR Exx-Series™*  
E53 | E75 | E85 | E95



# BRILLIANCE AT WORK



FLIR redesigned the Exx-Series from the handle up to deliver the best performance, resolution, and sensitivity of any pistol-grip handheld thermal camera.

The new Exx-Series camera is packed with the features you need to detect the early signs of water intrusion, air leaks, and other building deficiencies before they cause serious damage.

#### FLIR Exx-Series cameras now offer:

- Up to 161,472 points of measurement
- UltraMax® processing for 4x pixel resolution\*
- Our best MSX® enhancement
- Laser distance meter improves autofocus, provides distance and on-screen area measurement†
- A larger, 4" display that's 33% brighter
- A responsive new interface
- Improved organization and reporting options

\*Not available for E53 model

† E85/E95 only



reddot award 2017  
best of the best

# UNPARALLELED PERFORMANCE



## See Greater Detail

- Vibrant LCD is 33% brighter than earlier models
- Large 4" display with 160° viewing angle
- Up to 464 x 348 true native IR resolution
- Improved FLIR MSX® image enhancement

## Focus Fast & True\*

- Laser-assisted autofocus improves accuracy for precise temperature measurements
- Continuous focus mode responds quickly, promotes safe one-hand use
- Autofocus and record functions separated to prevent accidental re-focusing

## Quickly Discover Building Deficiencies

- Detects temperature differences down to 30 mK
- True 42° FOV for wide area surveys with a single lens\*
- Measure area (m<sup>2</sup> or ft<sup>2</sup>) of moisture intrusion or air leak on-screen†

\*E75, E85, E95 only  
†E85, E95 only




The Exx-Series is packed with the high performance features you need to quickly detect and report hidden building deficiencies: superior temperature sensitivity; bright, bold on-screen imagery; razor-sharp focus; and a rapid-response user interface.

## Navigate Screens Easier

- Quick response capacitive touchscreen
- Updated GUI with improved flow and feedback
- Logical navigation on screen and in menus

## Document & Report Problems

- Embed moisture meter data through METERLiNK®
- Upload images and report critical issues over Wi-Fi
- Image annotation through voice, text, on-screen sketch, GPS tagging, and compass
- Enhanced image analysis and reporting through FLIR Tools+ software



Mic for voice annotation

Speaker plays back voice annotation

Vibrant, 4" optically-bonded PCAP touchscreen

Scratch-resistant Dragontrail™ cover glass

Li-ion battery for extended use times

Ergonomic new design for our most comfortable grip

Laser provides distance measurement and precise autofocus\*

Laser pointer provides visual guidance

True 42° FOV for wide area surveys with a single lens\*

Bright LED work lights improve image clarity in dim areas

5 MP digital camera now closer to thermal detector for superior MSX® enhancements

Separate Autofocus and Image Recording buttons\*


# HARD-WORKING DESIGN, FOR HARD-WORKING PROS

This sleek new design isn't just window-dressing. From the rubberized, water-tight chassis to the scratch-resistant Dragontrail™ cover glass LCD, the new Exx-Series is made to work hard all day long.

**FLIR Exx-Series™**  
E53 | E75 | E85 | E95

\*E75, E85, E95 only

# DESIGNED WITH YOU IN MIND



## The Best Lenses Need the Best Autofocus\*

FLIR took its cue from the digital camera industry when re-engineering the Exx-Series focus system. Whether you choose autofocus or continuous focus, the camera's precise laser-assisted focus and FLIR's innovative lenses ensure you get crisp results, for the most accurate temperature readings.

## Work Safer

Your job can take you up ladders and into crawl-spaces, so you need tools that can be used one-handed and worry-free. FLIR designed its new Exx-Series cameras to be tough enough to use every day, with simplified buttons and intuitive screens that allow you to focus on your work – instead of on the camera controls.

## Work Smarter

The new Exx-Series cameras produce standard radiometric JPEGs that can be opened and viewed without proprietary software. Image files produced by Exx-Series cameras are supported by FLIR's Software Development Kit (ATLAS SDK), so companies can use their own software and still support read-out of thermal measurements, METERLiNK® data, and other important parameters embedded within the image. Current and voltage measurements embedded in image files are also accessible.

\*E75, E85, E95 only

# TECHNICAL SPECIFICATIONS

Features By Camera	E53	E75	E85	E95
IR Resolution	240 × 180 (43,200 pixels)	320 × 240 (76,800 pixels)	384 × 288 (110,592 pixels)	464 × 348 (161,472 pixels)
UltraMax®	—	307,200 pixels	442,368 pixels	645,888 pixels
Object Temperature Range	-20°C to 120°C (-4°F to 248°F) 0°C to 650°C (32°F to 1200°F)	-20°C to 120°C (-4°F to 248°F) 0°C to 650°C (32°F to 1200°F) Optional 300°C to 1000°C (572°F to 1830°F)	-20°C to 120°C (-4°F to 248°F) 0°C to 650°C (32°F to 1200°F) 300°C to 1200°C (572°F to 2192°F)	-20°C to 120°C (-4°F to 248°F) 0°C to 650°C (32°F to 1200°F) 300°C to 1500°C (572°F to 2732°F)
Focus	Manual	Continuous, one-shot laser distance meter (LDM), one-shot contrast, manual	Continuous, one-shot laser distance meter (LDM), one-shot contrast, manual	Continuous, one-shot laser distance meter (LDM), one-shot contrast, manual
Field of View (FOV)	24° × 18°	42° × 32° (10 mm lens), 24° × 18° (18 mm lens), 14° × 10° (29 mm lens)	42° × 32° (10 mm lens), 24° × 18° (18 mm lens), 14° × 10° (29 mm lens)	42° × 32° (10 mm lens), 24° × 18° (18 mm lens), 14° × 10° (29 mm lens)
Lens Identification	—	Automatic	Automatic	Automatic
Time-lapse (Infrared)	—	—	—	10 sec to 24 hours
Laser Area Measurement	—	—	Yes	Yes
Laser Distance Measurement	—	Yes, on-screen	Yes, on-screen	Yes, on-screen
Measurement Presets	No measurement, center spot, hot spot, cold spot, 3 spots, hot spot-spot*	No measurement, center spot, hot spot, cold spot, User Preset 1, User Preset 2	No measurement, center spot, hot spot, cold spot, User Preset 1, User Preset 2	No measurement, center spot, hot spot, cold spot, User Preset 1, User Preset 2
Spotmeter	3 in live mode	1 in live mode	3 in live mode	3 in live mode
Area	1 in live mode	1 in live mode	3 in live mode	3 in live mode
Picture-in-Picture	Centered infrared area on the visual image	Resizable and movable	Resizable and movable	Resizable and movable

\*Hot spot to center spot Delta measurement

Exx-Series cameras are backed by FLIR's industry-leading warranty

2 years: Full protection, parts, labor

10 years: Detector



\*After product registration on www.flir.com

FLIR Exx-Series™

Common Features	
Detector Type and Pitch	Uncooled microbolometer, 17 μm
Thermal Sensitivity/NETD	<0.04°C @ 30°C (86°F), 24° lens
Spectral Range	7.5 – 14.0 μm
Image Frequency	30 Hz
F-Number	f/1.3, 24° lens
Digital Zoom	1-4x continuous
Image Presentation and Modes	
Display	4", 640 × 480 pixel touch screen LCD with auto-rotation
Digital Camera	5 MP, 53° × 41° FOV
Color Palettes	Iron, Gray, Rainbow, Arctic, Lava, Rainbow HC
Image Modes	Infrared, visual, MSX®, Picture-in-Picture
MSX®	Embosses visual details on full resolution thermal image
Measurement and Analysis	
Accuracy	±2°C (±3.6°F) or ±2% of reading for ambient temperature 15°C to 35°C (59°F to 95°F) and object temperature above 0°C (32°F)
Alarms	Moisture, insulation, and measurement
Color Alarm (Isotherm)	Above/below/interval/condensation/insulation
Compass, GPS	Yes; automatic GPS image tagging
METERLINK®	Yes; several readings
Laser Pointer	Yes; dedicated button
Image Storage	
Storage Media	Removable SD card (8 GB)
Image File Format	Standard JPEG with measurement data included
Video Recording and Streaming	
Radiometric IR Video Recording	Real-time radiometric recording (.csq)
Non-Radiometric IR or Visual Video	H.264 to memory card
Radiometric IR Video Streaming	Yes, over UVC or Wi-Fi
Non-Radiometric IR Video Streaming	H.264 or MPEG-4 over Wi-Fi; MJPEG over UVC or Wi-Fi
Communication Interfaces	USB 2.0, Bluetooth, Wi-Fi, DisplayPort
Video Out	DisplayPort over USB Type-C
Additional Data	
Battery Type	Li-ion battery, charged in camera or on separate charger
Battery Operating Time	Approx. 2.5 hours at 25°C (77°F) ambient temperature and typical use
Operating Temperature Range	-15°C to 50°C (5°F to 122°F)
Storage Temperature Range	-40°C to 70°C (-40°F to 158°F)
Shock/Vibration/Encapsulation; Safety	25 g / IEC 60068-2-27, 2 g / IEC 60068-2-6, IP 54 / IEC 60529; EN/UL/CSA/PSE 60950-1
Weight/Dimensions	1 kg (2.2 lbs), 27.8 × 11.6 × 11.3 cm (11.0 × 4.6 × 4.4 in)
Box Contents	
	Infrared camera with lens, battery (2 ea), battery charger, front protection, straps (hand, wrist), hard transport case, lanyards, lens caps, lens cleaning cloth, power supplies, 8 GB SD card, Torx wrench, cables (USB 2.0 A to USB Type-C, USB Type-C to USB Type-C, USB Type-C to HDMI)

Specifications are subject to change without notice. For the most up-to-date specs, go to [www.flir.com](http://www.flir.com)



## The Infrared Training Center

The greater your knowledge about thermal imaging, the greater the dividends you'll realize for your company and your career. That's why the Infrared Training Center (ITC) offers classes for practically every application, from free online courses to advanced training that can certify you as a thermography expert, qualifying you to take a leadership role in your internal IR program.

- ITC classes include:
- Thermography Fundamentals Training
  - IR Building Inspection
  - IR Roofing Inspection

## Thermography Certification Training

Level I certifies that you know how a thermal imager works and how to use it. Level II cranks your credibility up a notch with more in-depth concepts and intensive labs. Level III asserts that you have knowledge and skills to administer your company's thermography program. These certifications offer strong validation to support the work you do as a thermographer.

Mobile Training Units and on-site training at your facility are encouraged if you would like to certify a group of 10 or more. For a complete list and schedule of courses and more information, visit [www.infraredtraining.com](http://www.infraredtraining.com).

**SWEDEN**

*Instruments Division*  
FLIR Systems AB  
Antennvägen 6  
187 66 Täby  
Tel. : +46 (0)8 753 25 00  
E-mail : flir@flir.com

**Benelux**

*Sales Administration*  
FLIR Commercial Systems  
Luxemburgstraat 2  
2321 Meer  
Belgium  
Tel.: +32 (0) 3665 5100

**FLIR Germany**

Frankfurt  
Tel. +49 (0)69 95 00 900

**FLIR Italy**

Milan  
Tel. +39 (0)2 99 45 10 01

**FLIR Spain**

Madrid  
Tel. +34 91 573 48 27

**FLIR Middle East**

Dubai  
Tel. +971 4 299 6898

**FLIR Africa**

Johannesburg  
Tel. +27 11 300 5622

**FLIR France**

Torcy  
Tel. +33 (0)1 60 37 01 00

**FLIR UK**

West Malling  
Tel. +44 (0)1732 220 011

**FLIR Russia**

Moscow  
Tel. + 7 495 669 70 72

**FLIR Turkey**

Istanbul  
Tel. +90 (212) 317 90 55

**For more information:**

flir@flir.com

www.flir.com  
NASDAQ: FLIR

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2018 FLIR Systems, Inc. All rights reserved. [03/18] 17-3307-INS BLD\_EMEA



The World's *Sixth Sense*®